

EarthBOUND®



An easy to use, environmentally safe mulch tackifier.

EarthBOUND® is recommended for use as a tackifier in re-vegetation applications where slow controlled irrigation will not create heavy runoff or erosion.

Mulch Tackifier Application Rates

EarthBOUND®

5 LB/AC

When mixing for use in hydroseed application, fill the tank 1/3 full with water, initiate agitation and slowly pour into tank while continuing to fill the tank. Add fiber, seeds and amendments after the tank is filled to the desired level.

EarthBOUND® Benefits

- Low application rates compared to plantago, starch and guar products.
- Cost savings – reduced costs for shipping, warehousing and installation.
- Thickened and consistent slurry sprays efficiently resulting in uniform application and coverage.
- Immediately bonds to soil during application resulting in less slumping.



For technical services or to locate your nearest EarthBOUND® dealer:



Call: **1-800-800-7671**

Email: **Sales@LSCenv.com**

Visit LSC online at: **www.LSCenv.com**

LSC Environmental Products, LLC

2183 Pennsylvania Ave., Apalachin, NY 13732

Information and statements herein are believed to be reliable but are not to be constructed as a warranty or guarantee. Some extreme situations may require higher application rates. LSC Environmental Products, LLC offers no warranties, express or implied. Nothing herein is to be taken as permission to practice any patented invention without a license. EarthBOUND® is a registered trademark of LSC Environmental Products, LLC. All rights reserved. © 2024 LSC Environmental Products, LLC

As with all soil stabilization, mulch and tackifier products, EarthBOUND® is designed for temporary site stabilization lasting a few days up to a couple of months. It is not designed to replace Hydraulic Erosion Control Products for seasonal control or winterization.

